





EU regulation 2016/425 attest n°0075/057/162/07/19/2234 delivered by CTC, notified body n°0075

TS1/T

MOUWEN – SNIJBESCHERMING LEVEL 3



PPE Category II

 EN 388	EN388:2016
Schuurweerstand : Snijbestendigheid : Scheurweerstand : Perforatieweerstand : Snijweerstand volgens ISO13997 :	Levels: ●●●○ ●●●○○ ●●●●● ●○○○ X
 EN 407	EN407
Brandgedrag: Contact hitte : Convection hitte : Stralingshitte : Kleine spetters gesmolten metaal : Grote spetters gesmolten metaal :	Levels: X ●○○○ X X X X
Lengte	Verpakt
50 cm	10/50

Mouw in 100% para-aramide stof. Elastisch uiteinde aan de bovenkant met klittenbandsluiting. Elastische pols in 100% para-aramide / elasthaan met duimgleuf. Lengte : 50 cm.

HET + PRODUCT

-  **AANPASSING**
-  **BESCHERMING**
-  **WEERSTAND**

RELEVANTE SECTOREN

-  Rubber
-  Engineering
-  Automotive
-  Metaal industrie
-  Assemblage
-  Glas



LEBON International S.à.r.l
 Immeuble Laccollth
 20, rue Eugène Ruppert L-2453 Luxembourg
 Website : www.lebonprotection.com
 TEL : +352 26 49 36 07
 FAX : +352 26 49 35 35