



CE
EN ISO 21420



4 X 4 4 F



X 1 X X X X

EU regulation 2016/425 attest n°0075/057/162/05/19/1602 – EXT 02/10/19 delivered by CTC, notified body n°0075



METALSAFE/R

CUT PROTECTION GLOVE LEVEL F



PPE Category II



EN388:2016 + A1:2018

	<u>Levels:</u>
Resistance to abrasion :	●●●●●
Blade cut resistance :	X
Tear resistance :	●●●●●
Puncture resistance :	●●●●●
Blade Cut resistance according to ISO13997 :	F



EN407:2020

	<u>Levels:</u>
Burning behaviour :	X
Contact heat :	●○○○○
Convective heat :	X
Radiant heat :	X
Small splashes of molten metal :	X
Large splashes of molten metal :	X

Sizes	Packaging
8 - 9 – 10 - 11	10/50

Full cow split leather glove. Black cow split leather on palm thickness 1.1/1.3 mm. Back in natural cow split leather. Lined with a seamless knitted glove 10 gauge, in 100% textra®/stainless steel thread.
15 cm natural cow split leather cuff with artery protector. 100% para-aramid sewing thread.

THE + PRODUCT



COMFORT



STABILITY



RESISTANCE

RELEVANT SECTORS



Automotive
manufacturing and
supply industry



Glass manufacturing and
processing industry



Metal manufacturing and
processing industry



Building and public works



Engineering industry and
industrial maintenance



LEBON International S.à.r.l
Immeuble Laccollith
20, rue Eugène Ruppert L-2453 Luxembourg
Website : www.lebonprotection.com
TEL : +352 26 49 36 07
FAX : +352 26 49 35 35