











LEBON. VALUE ADDED PARTNER

SHOCKPROTEC/F

CUT PROTECTION GLOVE LEVEL F



EN 388	EN388:2016
Resistance to abrasion: Blade cut resistance: Tear resistance: Puncture resistance: Blade Cut resistance according to ISO13997: Impact resistance:	Levels:

EN 407	EN407
Burning behaviour : Contact heat :	Levels: X ● ○○○
Convective heat: Radiant heat: Small splashes of molten metal: Large splashes of molten metal:	X X X X

Sizes	Packaging
6-7-8-9-10-11	10 per packet - 100 per box

PPE Category II

Seamless knitted glove, 10 gauge, in 100% high density polyethylene filament, 100% stainless steel filament and 100% black texturized polyamide. Grey CLEAN PU coating on palm and fingertips. New impact absorbent reinforcements on the back of the hand and the fingers for better flexibility and comfort. Elastic wrist.





THE + PRODUCT



DEXTERITY



RESISTANCE



REINFORCEMENT

RELEVANT SECTORS



Automotive manufacturing and supply industry



Engineering industry and industrial maintenance



Metal manufacturing and processing industry



Rubber manufacturing and processing industry



Building and public works



Assembly works



Glass manufacturing and processing industry

