

OCTOPUS®FIT/DA

CUT PROTECTION GLOVE LEVEL D



PPE Category II

EN 388 	EN388:2016 +A1:2018
Resistance to abrasion : Blade cut resistance : Tear resistance : Puncture resistance : Blade Cut resistance according to ISO13997 :	Levels: ●●●●● X ●●●●● ●●●●○ D
EN 407 	EN407:2020
Burning behaviour : Contact heat : Convective heat : Radiant heat : Small splashes of molten metal : Large splashes of molten metal :	Levels: X ●○○○○ X X X X
Sizes	Packaging
6 – 7 – 8 – 9 – 10 – 11 – 12	12 per packet - 120 per box

Seamless knitted glove, 13 gauge, with elasthane, 100% high density polyethylene filament, mineral filament and grey textured polyamide. First ¾ coating in grey nitrile for the waterproofness, second palm coating in black micro alveolate for a better grip. Nitrile patch between thumb and index for enhanced grip and durability. Elasticated wrist for a better comfort and fitting.

THE + PRODUCT

- 
RESISTANCE
- 
GRIP
- 
SEALING

RELEVANT SECTORS

- 
Automotive manufacturing and supply industry
- 
Engineering industry and industrial maintenance
- 
Metal manufacturing and processing industry
- 
Building and public works
- 
Glass manufacturing and processing industry
- 
Assembly works